

Panic Packs

Fixed Panic Panel



Specification:

Input Voltage Range:	110V ~ 230V AC 50Hz
Output Voltage:	13V ~ 14.4V Adjustable
Max Current output:	3.2A DC @ 14V
Relay contact rating:	10A
AC Fail output rating:	140mA Positive switching
Operating temp:	-3°C to 60°C
Dimensions (lxbxh):	200 x 180 x 80mm
Gross Weight:	0.895Kg
Warranty:	12 Months
Release date:	May 2013



FPP_Ver 4

- hard-wire panic input
- siren output
- radio trigger (N.O / N.C)
- ac fail trigger (+)
- strobe output
- intelligent battery charging
- 3 Amp Current output
- auto low battery cutout @10V DC when power fails

7A/H 12V Battery sold separately

Order Code

Fixed Panic Panel unit with 2 x Remotes

FPP2(C)

Applications

- Office panic
- Shop panic
- Home panic
- Factory panic
- Guard house panic

Features

- Microprocessor Controlled charging output.
- Low battery switch off at 10V DC.
- Buzzer tones on battery low and AC Fail.
- Resettable Fuse protection on output.
- Fuse protection on AC input.
- ABS Plastic enclosure.

Designed to be wired to a static hardwired panic button as well as work with Remote panic buttons. When a Panic is activated the unit will trigger the 3 Minute siren output as well as the Radio output & a Latching Strobe output. All activations can be reset via either the Remote control or the Hardwired Panic button. Our Low battery cutout @ 10V DC will safeguard the battery from deep discharge.