

# 6.4A Battery Backup

## Power-Supply



Fits 17A/H Battery.  
Battery sold separately

### Specification:

Input Voltage Range:	110V ~ 230V AC 50Hz
Output Voltage:	13V ~ 14.4V Adjustable
Max Current output:	6.4A DC / 70Watts
Relay contact rating:	10A
AC Fail output rating:	140mA Positive switching
Operating temp:	-3°C to 60°C
Dimensions (lxbxh):	315 x 230 x 100mm
Gross Weight:	1.30Kg
Warranty:	12 Months

### Certifications

EN 55022:2010; EN 55024:2010  
EN 6100-3-2:2006+A1:2009 + A2:2009  
EN 6100-3-3:2008; IEC 60950-1:2005 + A1:2009

### Order Code

6.4 AMP Power-Supply Battery  
charger with Low Battery Cut Out

6.4AMP

### Applications

- Alarm panel Battery backup
- CCTV Battery backup
- Backup power supply for door controller.
- Maglock for an Access Control solution

### Features

- Microprocessor Controlled charging output.
- Low battery switch off at 10V DC.
- Buzzer tones on battery low and AC Fail.
- 6 x Separate 1A Resettable Fuse protections outputs.
- Fuse protection on AC input.
- ABS Plastic enclosure.