

Standalone Transmitter

Features

- Code-Hopping Encryption
- 4-Channel telemetry outputs
- Normally open or Normally closed trigger inputs
- LED indication when a channel is triggered
- 1 or 3 transmit signals can be selected
- All inputs are supervised
- On/Off software functionality



- N.O / N.C. selection
- Pos / Neg input selection
- 1 or 3 signal bursts
- ON/OFF or Standard functionality

Specification:

Encryption:	Code-Hopping
Range:	1500m (Open air)
Frequency:	403MHz / 433MHz
Voltage Range:	9.8V to 16V DC
Current on TX:	>90mA
Current Standby:	>34mA
Dimensions(lxbxh):	187x104x67mm
Gross Weight:	235 grams
Operating Temp:	-3°C to 65°C
Warranty:	24 Months

Applications

- Transmission of Alarm signals
- Linking Electric Fence outputs to Alarms
- Switching On / Off Pumps on farms
- Industrial Machinery Control
- Wireless control of Generators

Certifications

- ETSI EN300 220_V2.4.1
- ETSI EN301-489-3 V1.41
- ETSI EN301-489-1 V1.92
- IEC 60950-1:2005 + A1:2009
- ICASA: TA-2017/1755

Order Codes

4 Channel Transmitter

S4