

Easy to press, splash proof, durable, long-range remote control for panic systems.

## Applications

- Frail care facilities nurse call
- Panic activation for shop keepers
- Response officer panic button
- Home panic button

## Features

- Big button designed for elderly & frail people
- Moisture proof design
- Unique antenna design incorporating the pendant chain to increase range
- 12V battery operation (23A Alkaline battery)
- LED flashes when there is a low battery condition

## Certifications

- ETSI EN300 220-V2.4.1
- ETSI EN301-489-3 V1.4.1
- ETSI EN301-489-1 V1.9.2
- IEC 60950-1:2005 + A1:2009
- EN 55022:2010; EN 55024:2010
- EN 6100-3-2:2006+A1:2009 + A2:2009
- EN 6100-3-3:2008; IEC 60950-1:2005 + A1:2009
- ICASA: TA-2017/2237



## Specifications

- Encryption: Code-Hopping
- Range: 500m (Open air)
- Frequencies: 403MHz / 433MHz
- Voltage Range: 10V to 13V DC
- Current draw: 32mA
- Dimensions (lxbxh): 70 x 37 x 18mm
- Gross Weight: 31 grams
- Operating Temp: -3°C to 65°C
- Warranty: 24 Months

| Description                 | Order Code |
|-----------------------------|------------|
| Panic Pendant Remote 403MHz | PTX1       |
| Panic Pendant Remote 433MHz | PTX1_433   |
| Wall Mount bracket          | WB         |
| 12V Replacement battery     | GP23A      |