

# Passive iR Transmitter Module



Designed to fit into most PIR motion detectors. Easy solution to creating wireless zones.

## Applications

- Transmission of battery powered PIR's
- Transmission of magnetic door contacts
- Emergency break glass boxes
- Roller shutter door contacts

## Features

- Alarm and Tamper transmit outputs (2 Channels)
- Powered by 2 x AA Alkaline batteries
- Battery life under normal conditions 3 years or
- 150 000 triggers
- 120 sec Sleep mode on/off
- Normally Open or Normally Closed

## Certifications

- ETSI EN300 220-V2.4.1
- ETSI EN301-489-3 V1.4.1
- ETSI EN301-489-1 V1.9.2
- IEC 60950-1:2005 + A1:2009
- ICASA: TA-2017/1845

Description	Order Code
PIR Transmitter + 2x AA batteries	PIR_TX_V2
PIR Transmitter + 2x AA batteries	PIR_TX_V2_433
AA Alkaline battery 1.5V	AA



\*Image for illustration purposes only  
PIR not included; Batteries not included

## Specifications

- Encryption: Code-Hopping
- Range: 500m (Open air)
- Frequencies: 403MHz / 433MHz
- Voltage Range: 2.2V to 4.5V DC
- Current on TX: +/-14mA
- Sleep mode: +/-400nano A
- Dimensions: (lxbxh) 71 x 31 x 28mm
- Gross Weight: 74 grams
- Operating Temp: -3°C to 65°C
- Warranty: 24 Months