

# Fixed Mount Transmitter - Indoor



## The Single Channel Wireless Stand Alone Transmitter.

### Applications

- Transmission of Alarm signals
- Linking Electric Fence outputs to Alarms
- Switching On / Off Pumps on farms
- Industrial Machinery Control
- Wireless control of Generators

### Features

- Code-Hopping Encryption
- 1-Channel outputs
- 12V DC
- Positive / Negative trigger
- Normally open or Normally closed inputs
- LED indication when the unit is triggered

### Certifications

- ETSI EN300 220-V2.4.1
- ETSI EN301-489-3 V1.4.1
- ETSI EN301-489-1 V1.9.2
- IEC 60950-1:2005 + A1:2009
- ICASA: TA-2017/1755

Description	Order Code
1 Ch Box Transmitter 403MHz	S1
1 Ch Box Transmitter 433 MHz	S1_433



### Specifications

- Encryption: Code-Hopping
- Range: 500m (Open air)
- Frequencies: 403MHz / 433MHz
- Voltage Range: 9.8V to 16V DC
- Current on TX: +/-30mA
- Sleep mode: +/-9mA
- Dimensions: (lxbxh) 187 x 104 x 67mm
- Gross Weight: 50 grams
- Operating Temp: -3°C to 65°C
- Warranty: 24 Months